FISH REFRIGERATED CABINETS

► STATIC ► CHILLER



GENERAL FEATURES

| GN2/1 Refrigerated upright cabinet (FISH) | • |
|---|---|
| Stainless Steel exterior and interior | • |
| Static cooling system with fan assisted cooling | • |
| Condenser with anti-corrosion treatment | • |
| Bottom side engine room (for comfortable storage in the cabinet) | • |
| Automatic compressor cycle defrost | • |
| Digital thermostat with "opening door" and "High temperature" alarm | • |
| Foaming Agent Cyclopentane (80mm) | • |
| Removable Gasket | • |
| LED light and lock fitted as standard | • |
| Door: Self closing and reversible door fitted as standard | • |
| N.8 Pans "fish water drain trayn" antioxidation included | • |
| Plastic thermal-braker anti-condensation as chamber body frame | • |
| N.4 Adjustable feet - S/S feet or castor with brake (Option) | • |
| Energy efficiency class: D | • |
| | |

TECHNICAL SPECIFICATIONS

| Capacity | 600 L |
|----------------------------------|--------------|
| Temperature | -7° ~ +2°C |
| Consumption | 2.5 kWh/24h |
| Rated Power | 350 W |
| Noise level | 48 dB(A) |
| Net Weight | 150 Kg |
| Gross Weight | 161 Kg |
| External Dimensions (WxDxH mm) | 740x880x2025 |
| Internal Dimensions (WxDxH mm) | 580x710x1430 |
| Packaging dimensions (WxDxH mm) | 760x900x2150 |
| Loading quantities 20'/40'/40'HQ | 18/39/39 |

(E C

RoHS

CERTIFICATION



QRX 688FH



















DETAILS







Stainless steel feet

Digital thermostat and door lock fitted as standard

Foamed door

















Anti-tipping shelves guide included Pans with fish water drain tray (Antioxidation)

Bottom hole for easily clean and dry the item

PRODUCT DIMENSIONS



